

60 DC Blower

× 60 × 15mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量		静压		噪音
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H2O	In-H2O	dba
SP60B05L-15DL	B/S	5	4.5~5.5	0.16	0.80	3500	0.10	3.55	10.80	0.45	27.0
SP60B12L-15DL	B/S	12	7.0~13.2	0.13	1.56	3500	0.10	3.55	10.80	0.45	27.0
SP60B24L-15DL	B/S	24	14.0~26.4	0.07	1.68	3500	0.10	3.55	10.80	0.45	27.0
SP60B05M-15DL	B/S	5	4.5~5.5	0.20	1.00	4000	0.11	3.85	11.50	0.45	31.0
SP60B12M-15DL	B/S	12	7.0~13.2	0.20	2.40	4000	0.11	3.85	11.50	0.45	31.0
SP60B12H-15DL	B/S	12	7.0~13.2	0.25	3.00	4600	0.13	4.45	15.53	0.61	35.0
SP60B24H-15DL	B/S	24	14.0~26.4	0.10	2.40	4600	0.13	4.45	15.53	0.61	35.0

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

